

CLAIMS

1. A reversible necktie comprising:
at least two fabrics stitched together.
2. The reversible necktie of claim 1 wherein an inner lining is located between said two fabrics.
3. The reversible necktie of claim 1 wherein said at least two fabrics are stitched together by series of run stitches.
4. The reversible necktie of claim 1 further comprising a first necktie shaped section containing a rectangular end and a second necktie shaped section containing a rectangular end.
5. The reversible necktie of claim 4 wherein said first necktie shaped section and said second necktie shaped section are stitched together at said rectangular ends.
6. The reversible necktie of claim 1 wherein said first necktie shaped section and said second necktie shaped section are stitched together by series of zig-zag stitches.
7. The reversible necktie of claim 4 wherein a third rectangular shaped section is stitched to the rectangular ends of said first necktie shaped sections and said second necktie shaped sections.
8. The reversible necktie of claim 7 wherein said third rectangular shaped section is stitched to said first and second necktie shaped sections using a series of zig-zag stitches.
9. The reversible necktie of claim 1 further comprising a first and a second side edge, a first and second upper edge and at least one lower edge.
10. The reversible necktie of claim 7 wherein said at least one lower edge possesses a satin stitch.

11. The reversible necktie of claim 9 further comprising two lower edges.
12. The reversible necktie of claim 11 wherein said two lower edges possess a satin stitch.
13. A method of manufacturing a reversible necktie comprising:
 - placing a first piece of fabric on top of a second piece of fabric;
 - drawing an outline of at least two necktie shaped sections on said first piece of fabric, said outline including a first and second side edge, a first and second upper edge and a lower edge;
 - stitching said at least two necktie shaped sections to connect said first piece of fabric and second piece of fabric substantially together along said first and second side edges of said outline and said first and second upper edges of said outline with a run stitch;
 - cutting said stitched together outline of a necktie from said first piece of fabric and second piece of fabric;
 - placing an inside lining on top of said stitched together outline of a necktie from said first piece of fabric and second piece of fabric;
 - pulling said stitched together outline of a necktie through said lower edge of the stitched together first piece of fabric and second piece of fabric unstitched.
 - placing said at least two necktie shaped sections end to end;
 - stitching together said lower ends of said at least two necktie shaped sections utilizing a zig-zag stitch;
 - ironing said stitched together outline of a necktie.
14. A method of manufacturing a reversible necktie comprising:

placing a first piece of fabric on top of a second piece of fabric;

drawing an outline of a necktie on said first piece of fabric, said outline including a first and second side edge, a first and second upper edge and a first and second lower edge;

stitching said outline of said necktie through said first piece of fabric and second piece of fabric together along said first side edge, said first and second upper edges and said first and second lower edges of said outline with a run stitch;

stitching said second side edge substantially, leaving an unstitched area;

cutting said stitched together outline of a necktie from said first piece of fabric and second piece of fabric;

placing an inside lining on top of said stitched together outline of a necktie;

pulling said stitched together outline of a necktie inside out through said unstitched area;

placing a run stitch in said unstitched area;

ironing said stitched together outline of a necktie.

15. A method of manufacturing a reversible necktie comprising:

placing a first piece of fabric on top of a second piece of fabric;

drawing an outline of a necktie on said first piece of fabric, said outline including a first and second side edge, a first and second upper edge and a first and second lower edge;

stitching said outline of said necktie through said first piece of fabric and second piece of fabric together along said first and second side edge, said first and second upper edges with a run stitch;

cutting said stitched together outline of a necktie from said first piece of fabric and second piece of fabric;

placing an inside lining on top of said stitched together outline of a necktie;

pulling said stitched together outline of a necktie inside out through said unstitched a first and second lower edge area;

placing a satin stitch in said first and second end;

ironing said stitched together outline of a necktie.

16. A method of manufacturing a reversible necktie comprising:

placing a first piece of fabric on top of a second piece of fabric;

drawing an outline of a necktie on said first piece of fabric, said outline including a first and second side edge, a first and second upper edge and a first and second lower edge;

stitching said outline of said necktie through said first piece of fabric and second piece of fabric together along said first and second side edge and said first and second upper edges with a run stitch;

cutting said stitched together outline of a necktie from said first piece of fabric and second piece of fabric, creating a first flap on said first piece of fabric and a second flap on said second piece of fabric;

placing an inside lining on top of said stitched together outline of a necktie;

pulling said stitched together outline of a necktie inside out through said unstitched area;

folding said first and second flap inside said stitched together outline of a tie;

placing a run stitch in said first and second lower edge;

ironing said stitched together outline of a necktie.